



## Pro Series

"High Speed Long Range Face Recognition"



**Face Capacity** 5000





**RFID Capacity** 5000















Finger Capacity 5000





**PIN Capacity** 5000







## Biometrics with GPS

Specification	Company Specs
CDII	105 10 45140 4 47 111
CPU	1.2 Dual Core ARM Cortex-A7 or higher
NPU	600G (0.6T) or higher
RAM	256M DDR3L or higher
ROM	4G EMMC or higher
Camera	Real Sensor 2MP HD Color camera
Fill Light	LED fill light and dual infrared fill light (Automatic control according to ambient high)
Display	5.0-inch IPS touch screen, HD 720 x 1280 or higher
Communication Port	TCP/IP, USB type A (Support u disk), WiFi
_	Support
Backup Battery	
Power	DC 12V, 2A
Working Temperature	-20 to +45C
Material	Aluminum/metal which shall work in - 20 degree celsius allow case
OS	Linux 3.0 or higher
Language	English, Hindi
QR Code Scanner	Support (Scan by camera)
Face/Card/Password Capacity	Minium 5,000
Fingerprint Capacity	Minium 10,000
Logs Capacity	Minium 500000
Face Recognition Speed	<0.25
Face Recognition Distance	0.5-2.5 meters (adjustable)
Live Face Detection	Reject photo and video
Mask Detection	Support mask detection and face
Polay Output	recognition with wearing mask
Relay Output	one set
Alarm Output	one set
Fire Input	one set
Door Sensor	Support
Wiegand	One set WG 26/34 Input/output
Exit Button	Support